




# Garmin GPS V Display Replacement

This guide explains how to replace the display assembly.

Written By: Connor



 **TOOLS:**


- Phillips #0 Screwdriver (1)
  - Phillips #1 Screwdriver (1)
  - Soldering Workstation (1)
  - Spudger (1)
-

## Step 1 — Logic Board




- Orient the GPS V backside up.
- With a #0 Philips screwdriver, remove six M2x0.4 black screws on the back of the unit.

## Step 2





- With the spudger, gently pry the back plate off the unit starting at the corners.
- Open the back plate about 35°, use the antenna side act like a hinge.
- ⚠ Do **NOT** remove the back plate all the way, there are cables connected to it.

### Step 3



- Locate the white 8-pin connector on the logic board and disconnect it.
- Open the device all the way, making sure to not disconnect the brown antenna wire.


### Step 4



- With a #1 Philips screwdriver, remove the silver M2x0.4 screw on the logic board near the brown wire.
- ⓘ You may need to rotate the device to get better access to the screw.


This document was generated on 2021-05-28 04:04:37 AM (MST).

## Step 5




- Locate the ribbon connector on the logic board.
- With the spudger, gently apply pressure to both sides of the brown connector lock until it pushes out.
- With the spudger, gently work the ribbon cable out of the connector until it is free.

## Step 6





- With the spudger, gently pry out the logic board.
- ⚠ Be careful to not disconnect the brown antenna wire as you remove the logic board.

## Step 7




- Locate the brown wire connection on the logic board.
- Carefully apply heat with the soldering iron while gently pulling on the brown wire.
- ⓘ It may take some time to heat the flux up before the wire can be pulled out.
- Pull brown wire free of the logic board.

## Step 8 — Button Pad



- Gently pry the button pad off of the front plate.

## Step 9 — Display



- Orient the front plate of the device so the display board is facing up.
- With the spudger, gently work your way around the display assembly.
- ⓘ NOTE: The display assembly is composed of three parts and is glued to the case. Be careful to not separate it when prying it out.
- Pry the display free of the front plate.

To reassemble your device, follow these instructions in reverse order.