



# HTC Hero Camera Replacement

Written By: Max Brown



## TOOLS:

iFixit Opening Tool (1)  
T6 Torx Screwdriver (1)  
Tweezers (1)

## PARTS:

OEM HTC Hero Camera (1)

### Step 1 — Back Case



- Remove the back of the phone by pushing firmly with your thumbs up towards the camera.
- Remove both the battery and the SD card (Press SD card in to release)
- Locate and remove the four Torx screws highlighted in the photo, with the phone laying face down on your work space.

### Step 2



- **Carefully** pry the inside back cover from the device using an appropriate size plastic opening tool or small flathead screwdriver.
- Insert the flat end between the back and front enclosure, working your way around the rim.

### Step 3



- **Gently** depress and release the small plastic tabs around the rim in the front enclosure, highlighted here.

ⓘ It is best to start with the tab found on the top center of the phone, as it is easiest to locate.


### Step 4



- **Carefully** separate the front and back enclosures once all of the clips have been disengaged.


⚠ Be sure to not separate too quickly or you risk breaking an attached tab.

## Step 5 — Camera



- Locate the four metal tabs on the top and bottom of the camera holding the camera enclosure to the motherboard.

## Step 6



- Using a pair of metal [tweezers](#), simultaneously depress both tabs on one side of the camera enclosure and **gently pull up** until tabs come free. Repeat for the opposite side.





## Step 7



- Pull the released camera enclosure away from the motherboard until it is completely free.

## Step 8



- Now with camera unit exposed, **gently wiggle the camera** as you pull away from the phone to remove it.

---

To reassemble your device, follow these instructions in reverse order.